

# **DECLARATION OF PERFORMANCE**

Construction Products Regulation (CPR) No 305/2011

Nº R002

## 1. UNIQUE IDENTIFICATION OF THE PRODUCT TYPE

BEYEM B-P. Type OC CSIV W<sub>c</sub> 2

#### 2. MANUFACTURER

Rodacal Beyem, Ctra Madrid -Alicante, Km 213 (Extramuro) 02630 La Roda, Albacete, Spain. www.rodacal.com

#### INTENDED USE

Coloured one coat mortar based on hydraulic binders and suitable for exterior and interior use. Projected aggregate finish.

#### 4. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE OF THE PRODUCT

Δ

## 5. HARMONISED STANDARD

EN 998-1:2016

## 6. NOTIFIED BODY

Not applicable

## 7. DECLARED PERFORMANCE

Essential characteristics	Performance	Harmonised technical specification
Compressive strength	CSIV	EN 998-1:2016
Reaction to fire	A1	
Capillary water absorption	W <sub>c</sub> 2	
Water permeability after weathering cycles	≤ 1 ml/cm², after 48 h	
Water vapour permeability	µ≤ 15	
Adhesion after weathering cycles	≥ 0,3N/mm <sup>2</sup> A,B fracture	
Thermal conductivity	$\lambda_{dry}$ = 0,40 W/ m*k (Tabulated value P=50%)]	
Hazardous substances	See MSDS	

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

All information referring to use conditions and storage must be consulted in the Technical Data Sheet





Signed for and on behalf of the manufacturer by:

CE

Victorina García Escribano General Manager

La Roda, 20/07/2018