

**DECLARATION OF PERFORMANCE**  
Construction Products Regulation (CPR) No 305/2011

Nº R017

**1. UNIQUE IDENTIFICATION OF THE PRODUCT TYPE**

BEYEM NEOCAL MURO. Type CR CSII W<sub>c</sub> 1

**2. MANUFACTURER**

Rodacal Beyem, Ctra Madrid –Alicante, Km 213 (Extramuro) 02630 La Roda, Albacete, Spain. www.rodacal.com

**3. INTENDED USE**

Rendering mortar based on natural hydraulic lime suitable for exterior and interior use.

**4. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE OF THE PRODUCT**

4

**5. HARMONISED STANDARD**

EN 998-1:2016

**6. NOTIFIED BODY**

Not applicable

**7. DECLARED PERFORMANCE**

Essential characteristics	Performance	Harmonised technical specification
Compressive strength	CSII	EN 998-1:2016
Reaction to fire	A1	
Capillary water absorption	W <sub>c</sub> 1	
Water vapour permeability	μ ≤ 15	
Adhesion	≥ 0,20 N/mm <sup>2</sup> B fracture	
Thermal conductivity	λ <sub>dry</sub> = 0,53 W/ m*k (Tabulated value P=50%)	
Hazardous substances	See MSDS	

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

All information referring to use conditions and storage must be consulted in the Technical Data Sheet

Signed for and on behalf of the manufacturer by:



Victorina García Escribano  
General Manager



La Roda, 14/06/2019