

DECLARATION OF PERFORMANCE

Construction Products Regulation (CPR) No 305/2011

Nº R007

1. UNIQUE IDENTIFICATION OF THE PRODUCT TYPE

BEYEM NEOCAL FINO. Type CR CSII $\mathrm{W_c}\,2$

2. MANUFACTURER

Rodacal Beyem, Ctra Madrid - Alicante, Km 213 (Extramuro) 02630 La Roda, Albacete, Spain. www.rodacal.com

3. INTENDED USE

Rendering and plastering coloured mortar based on non-hydraulic lime and mixed binders and suitable for exterior and interior use.

4. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE OF THE PRODUCT

Λ

5. HARMONISED STANDARD

EN 998-1:2016

6. NOTIFIED BODY

Not applicable

7. DECLARED PERFORMANCE

Essential characteristics	Performance	Harmonised technical specification
Compressive strength	CSII	
Reaction to fire	A1	
Capillary water absorption	W _c 2	
Water vapour permeability	μ ≤ 15	EN 998-1:2016
Adhesion	≥ 0,15N/mm ² A,B fracture	
Thermal conductivity	λ_{dry} = 0,75 W/ m*k (Tabulated value P=50%)]	
Hazardous substances	See MSDS	

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

All information referring to use conditions and storage must be consulted in the Technical Data Sheet





Signed for and on behalf of the manufacturer by:

Oscica

Victorina García Escribano

General Manager

 ϵ

La Roda, 20/07/2018