

DECLARATION OF PERFORMANCE

Construction Products Regulation (CPR) No 305/2011

Nº AL002

1. UNIQUE IDENTIFICATION OF THE PRODUCT TYPE

Beyem M-15. Type G M15

2. MANUFACTURER

Rodacal Beyem, Ctra Madrid –Alicante, Km 213 (Extramuro) 02630 La Roda, Albacete, Spain. www.rodacal.com

3. INTENDED USE

Factory made masonry mortar (bedding, jointing and pointing) for use in masonry walls, columns and partitions.

4. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE OF THE PRODUCT

2+

5. HARMONISED STANDARD

EN 998-2:2016

6. NOTIFIED BODY

AENOR nº 0099. Certification of conformity of factory production control. System 2+. Nº0099/CPR/A69/0048. Date of issue 27/01/2005.

7. DECLARED PERFORMANCE

Essential characteristics	Performance	Harmonised technical specification
Compressive strength	M15	EN 998-2:2016
Bond strength		
Shear bond strength	0.15 N/mm ² (Tabulated value)	
Flexural bond strength	0.15 N/mm ² (Tabulated value)	
Reaction to fire	A1	
Capillary water absorption	0,4 kg/m ² min ^{1/2}	
Water vapour permeability	μ= 15/35 (Tabulated value)	
Thermal conductivity	λ _{dry} = 1,17 W/ m*k (Tabulated value P=50%)	
Hazardous substances	See MSDS	

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

All information referring to use conditions and storage must be consulted in the Technical Data Sheet

Signed for and on behalf of the manufacturer by:



Victorina García Escribano
General Manager



La Roda, 09/09/2019