

## DECLARATION OF PERFORMANCE

Construction Products Regulation (CPR) No 305/2011

Nº AL003

**1. UNIQUE IDENTIFICATION OF THE PRODUCT TYPE**

BEYEM NEOCAL MUR

**2. MANUFACTURER**

Rodacal Beyem, Ctra Madrid –Alicante, Km 213 (Extramuro) 02630 La Roda, Albacete, Spain. www.rodacal.com

**3. INTENDED USE**

Factory made prescribed masonry mortar for use in masonry walls, columns and partitions.

**4. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE OF THE PRODUCT**

4

**5. HARMONISED STANDARD**

EN 998-2:2010

**6. NOTIFIED BODY**

Not applicable

**7. DECLARED PERFORMANCE**

Essential characteristics	Performance	Harmonised technical specification
Proportion of components	Portland Cement: 0% Aggregates: 70,5% Lime NHL 5: 25% Metakaolin: 2,5% Aditions: 2%	EN 998-2:2010
Reaction to fire	A1	
Capillary water absorption	0,5 kg/m <sup>2</sup> min <sup>1/2</sup>	
Water vapour permeability	M ≤ 15	
Thermal conductivity	λ <sub>dry</sub> = 0,96 W/ m*k (Tabulated value P=50%)	
Hazardous substances	See MSDS	

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

All information referring to use conditions and storage must be consulted in the Technical Data Sheet

Signed for and on behalf of the manufacturer by:



Victorina García Escribano  
General Manager



La Roda, 03/11/2017